

PressWhileNotFound

Description

Press on a certain element (ElementToClick) while another element (ElementToFind) is not found

Parameters

Name	Value	Description
Zone	String with one of the following values <ul style="list-style-type: none">NATIVEWEBTEXT	Zones which define the way the element will be identified.
ElementToClick	String	Query to identify the element to click
ElementToClickIndex	Integer	Index of Element
ElementToFind	String	Query to identify the element which is looked for.
Timeout	Integer	Waiting Timeout in milliseconds
Delay	Integer	The time to wait between rounds

Usage



Set Experitest Url

Please make sure you replace <EXPERITEST_URL> with appropriate URL in the sample code below.

- For SeeTest cloud, **EXPERITEST_URL** needs to be <https://cloud.seetest.io/wd/hub/>
- For Dedicated Experitest Lab, **EXPERITEST_URL** needs to be your own domain. e.g - <https://company.experitest.com>

Example

In this example till the element with text "Expense : 4" is not found Expenses will be added by pressing element with the text "Add".



PressWhileNotFound

```
DesiredCapabilities dc = new DesiredCapabilities();
driver = new AndroidDriver(new URL("<EXPERITEST_URL>"), dc);
seetest = new SeeTestClient(driver);
dc.setCapability(MobileCapabilityType.UID, "deviceid");

...
...

//Press till we fule element with text "Expense :4"
seetest.pressWhileNotFound("NATIVE", "text=Add", 0, "text=Expense :4", 0, 10000, 100);
```